

# 414VA

## Controllable louvre

GLAZED-IN  
LOUVRE

ALUMINIUM



414VA



414/D

### MATERIAL

- Made from aluminium sections: AlMgSi 0.5 [according to EN 12020-2]
- Stainless steel 304 mesh [2.3 x 2.3 mm]
- Finishing: anodized in satin colour [20 micron] or powder-coated in any RAL or Syntha Pulvin colour [40 micron]

### DIMENSIONS

- Blade pitch: 33,3 mm
- Frame thickness: 24, 28 or 32 mm
- Minimum dimensions: 200 x 130 mm
- Specify on ordering: width x height in mm [overall dimensions]
- Controllable in combination with 100, 130 and 150 mm hit-and-miss ventilators or with insulated aluminium door [414/D] [max size 400 x 400 mm]

### FIXING

- Suitable for 24, 28, 32 mm glazing sections. Other thicknesses on request.

### OPTIONS

- Stainless steel 304 mesh [6x6/10x10/20x20 mm] or without
- Insect screen or mesh in stainless steel 316

### CONTROL OPTIONS (1 CONTROL PANEL PER MODULE)

- Knob control [standard]
- Rod
- Cord
- Motor

## TECHNICAL SPECIFICATIONS

All properties are valid for the standard version of the Louvre, unless otherwise stated.

Airflow		[EN 13030]
K-factor [entry]		28.13
C <sub>e</sub> coefficient		0.189
<i>[For combinations with closable louvres 130 and 150 mm]</i>		



## TECHNICAL DRAWINGS

